PERRYTON

Prepared by the U. S. Army Topographic Command (BEPM), Washington, D. C. Compiled in 1956 by photogrammetric methods from aerial photographs taken 1954. Photographs field annotated 1954. Revised in 1975 by the U. S. Geological Survey from aerial photographs taken 1974.

Area covered by dashed light-blue pattern is subject to controlled inundation

100,000-foot grids based on Texas coordinate system, north zone and Oklahoma coordinate system, north zone.

Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES
- Over 500,000 — LOS ANGELES
- 100,000 to 500,000 — OMAHA
- 25,000 to 100,000 — GALVESTON
- 5,000 to 25,000 — Durango
- 1,000 to 5,000 — Grand Coulee
- Less than 1,000 — Sun Valley

RAILROADS — Single track / Double or Multiple
- Standard gauge
- Narrow gauge

BOUNDARIES
- International
- State
- County
- Park or reservation

ROADS
- Primary, all-weather, hard surface
- Secondary, all-weather, hard surface
- Light-duty, all-weather, hard or improved surface
- Fair or dry weather, unimproved surface
- Trail
- Interchange

Route markers: Interstate, U.S., State

- Landmark: School; Church; Other,
- Mine
- Spot elevation in feet
- Marsh or swamp
- Intermittent or dry stream
- Power line
- Landplane airport
- Landing area
- Seaplane airport
- Ss-plane anchorage
- Woods-brushwood

Scale 1:250,000

5 0 5 10 15 20 Statute Miles

5 0 5 10 15 20 25 30 Kilometers

5 0 5 10 15 Nautical Miles

CONTOUR INTERVAL 100 FEET
WITH SUPPLEMENTARY CONTOURS AT 50 FOOT INTERVALS

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 14

1975 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 10½° (190 MILS) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 9½° (170 MILS) EASTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092

USGS NMD HISTORICAL MAP
OCT 15 1987
REC'D FILE COPY

LOCATION DIAGRAM

NJ 13-5 PUEBLO	NJ 13-6 LAMAR	NJ 14-4 SCOTT CITY	NJ 14-5 GREAT BEND	NJ 14-6 HUTCHINSON
COLORADO NJ 13-8 TRINIDAD	NJ 13-9 LA JUNTA	DODGE CITY NJ 14-7	KANSAS PART OF NJ 14-8	WICHITA NJ 14-9
RATON NJ 13-11	NJ 13-12 DALHART	NJ 14-10 PERRYTON	NJ 14-11 WOODWARD	NJ 14-12 ENID
NEW MEXICO SANTA FE NI 13-2	NI 13-3 TUCUMCARI	NI 14-1 AMARILLO	NJ 14-2 CLINTON	OKLAHOMA OKLAHOMA CITY NI 14-3
NI 13-5 FORT SUMNER	NI 13-6 CLOVIS	TEXAS NI 14-4 PLAINVIEW	NI 14-5 LAWTON	NI 14-6 ARMORE

SECTIONIZED TOWNSHIP

6	5	4	3	2	1	
7	8	9	10	11	12	
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

TOWNSHIP OR RANGE LINE

LAND GRANT BOUNDARY

GRID ZONE DESIGNATION: 14S

100,000 M. SQUARE IDENTIFICATION: KR LR MR / KQ LQ MQ

IGNORE the SMALLER figures of any grid number; these are for finding the full coordinates. Use ONLY the LARGER figure of the grid number. example: 3900000

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1000 METERS

SAMPLE POINT: MORSE

	KQ
	7 7
	9 4

1. Read letters identifying 100,000 meter square in which the point lies.
2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself. Estimate tenths from grid line to point.
3. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself. Estimate tenths from grid line to point.

SAMPLE REFERENCE: KQ7794

If reporting beyond 10° in any direction, prefix Grid Zone Designation, ex: 14SKQ7794

INTERIOR—GEOLOGICAL SURVEY, RESTON, VIRGINIA—1977

PERRYTON, TEXAS; OKLAHOMA; KANSAS

1954

REVISED 1975