



Making a Feral Hog Snare

Chancey Lewis, Matt Berg, Nikki Dictson, Jim Gallagher, Mark McFarland, and James C. Cathey*

Increasing populations of feral hogs in Texas are damaging landscapes, agricultural production, water quality, and native plant and animal communities. To reduce these problems, snaring can be an easy, inexpensive part of a feral hog management strategy.

Snares can be used when a single hog needs to be captured and where larger traps are impractical. Because snares are easy to assemble, many landowners make their own.

Materials needed


To make a hog snare, you will need the following tools and materials (Fig. 1):

- Needle-nose pliers
- Hammer
- Cable cutters
- Tape measure
- 10 feet of $\frac{1}{8}$ -inch steel cable
- Two $\frac{1}{8}$ -inch single ferrules
- One $\frac{1}{8}$ -inch double ferrule
- One R 6/0 barrel swivel
- One $\frac{1}{8}$ -inch snare or cam lock

Steps for building a snare

When building a feral hog snare, keep in mind that the cable used to make snares has a natural lay, or memory. Do not go against the memory of the cable when working with snares.

Figure 1



Materials for creating a feral hog snare.

Figure 2



Run the cable through the snare lock.

1. Feed the cable through the snare lock (Fig. 2). For this example, a $\frac{1}{8}$ -inch snare lock is used. There are many different lock designs, and some people make their own.
2. Take a single ferrule and crimp it to the end of the cable (Fig. 3). This can be accom-

*Former Extension Assistant; Extension Program Specialist; Extension Program Specialist II; Assistant Extension Wildlife Specialist; Professor and Extension Soil Fertility Specialist; and Associate Professor and Extension Wildlife Specialist All of The Texas A&M University System

Figure 3



Run the cable through the snare lock.

Figure 4



Reverse bend above single ferrule to secure the snare lock.

plished by using fencing crimpers or a hammer and hard surface.

- Using needle-nose pliers, make a reverse bend in the cable just beneath the ferrule (Fig. 4). This will be the only time that the cable is bent against the memory. The reverse bend helps secure the lock.
- Load the snare. Simply find a durable round or cylindrical object such as a pipe or vice handle. For the snare in this example, the trailer ball on a receiver hitch was used. When loading the snare, it is critical that the natural memory of the cable is followed. Only 8 to 10 inches beyond the ferrule stop needs to be loaded. This serves two purposes: 1) it gives the snare a more circular shape, which is important to capture animals with large, pointy ears like those of hogs, and 2) it enables the snare to close much more easily and freely.

- Move the snare back and forth, applying firm pressure near the stop while gradually lessening the pressure down the cable near the 10 inch mark (Fig. 5). An unloaded snare has a teardrop shape; a loaded snare is much rounder (Fig. 6).
- Next, construct the end so that the snare can be attached to a tree, post, or drag. For this example, an adjustable end was made. An adjustable end can be altered to loop the end around various size objects; however, it will not swivel. To make an adjustable end snare, start by sliding a double ferrule over the end of the cable (Fig. 7A). Then run the cable back through the double ferrule (Fig. 7B).
- Use a hammer or crimpers to attach a single ferrule to the end, creating the desired configuration (Fig. 8). A swivel end may be attached with two single ferrules for strength. Having an adjustable end is advan-



Figure 5



Load the snare by applying pressure as the cable is moved back and forth.

Figure 6

A constructed snare before the cable is loaded (A), and after (B).





tageous when setting snares on rubs or trees. The end can be opened, and the snare loop can be wrapped around the rub or tree and then back through the snare end, attaching the snare to the rub or tree.

Summary

Used as a complement to other approaches or in areas where larger traps are impractical, handmade snares can be a helpful tool in feral hog management. With simple tools and minimal hardware, snares can be made quickly at low cost, increasing their appeal in situations involving the capture of a single animal.

Figure 7



Create an adjustable end by sliding a double ferrule over the cable (A) then feeding the cable back through the double ferrule.

Figure 8



Attach a ferrule to the end of the cable (A). The snare can be designed with a swivel end (B-left) or an adjustable end (B-right).

Acknowledgment and disclaimer

This publication was developed as part of the Plum Creek Watershed Feral Hog Project, with funding support from the U.S. Environmental Protection Agency through a Clean Water Act §319(h) Nonpoint Source grant administered by the Texas State Soil and Water Conservation Board and from the Cooperative State Research, Education, and Extension Service, U.S. Department of Agriculture (USDA), National Integrated Water Quality Program. Any opinions, findings, conclusions, or recommendations expressed in this publication are those of the author(s) and do not necessarily reflect the view of the USDA.



Produced by Texas A&M AgriLife Communications

Extension publications can be found on the Web at <http://AgriLifeBookstore.org>

Visit Texas AgriLife Extension at <http://AgriLifeExtension.tamu.edu>

Educational programs of the Texas AgriLife Extension Service are open to all people without regard to race, color, sex, disability, religion, age or national origin.

Issued in furtherance of Cooperative Extension Work in Agriculture and Home Economics, Acts of Congress of May 8, 1914, as amended, and June 30, 1914, in cooperation with the United States Department of Agriculture. Edward G. Smith, Director, Texas AgriLife Extension Service, The Texas A&M University System.
12M, New